

Correction

Correction: Bedon, C.; Fasan, M. Reliability of Field Experiments, Analytical Methods and Pedestrian's Perception Scales for the Vibration Serviceability Assessment of an In-Service Glass Walkway. *Appl. Sci.* 2019, 9, 1936

Chiara Bedon *  and Marco Fasan 

Department of Engineering and Architecture, University of Trieste, 34127 Trieste, Italy; mfasan@units.it

* Correspondence: chiara.bedon@dia.units.it; Tel.: +39-040-558-3837

Received: 16 August 2019; Accepted: 26 January 2020; Published: 4 February 2020



We, the authors, wish to make the following corrections to our paper [1]

In Section 2.2 of the research paper *Appl. Sci.* 2019, 9, 1936; <https://doi.org/10.3390/app9091936>, the authors recall the fundamental aspects of structural dynamics for pedestrian systems, with special attention given to the analysis of Human Structure Interaction (HSI) effects.

In doing so, however, a misspelled equation of motion was described in Equation (1), with the expression:

$$M\ddot{x}(t) + C(t) + Kx(t) = P(t) \quad (1)$$

where M , C , and K represent the modal mass, damping, and stiffness matrices, respectively, $P(t)$ is the imposed external (periodic) force reproducing the motion of occupants, and $x(t)$ is the vertical displacement vector.

The correct, well-known equation of motion—that replaces the original Equation (1)—is the following:

$$M\ddot{x}(t) + C\dot{x}(t) + Kx(t) = P(t) \quad (1)$$

The authors apologize for the mistake.

Reference

1. Bedon, C.; Fasan, M. Reliability of Field Experiments, Analytical Methods and Pedestrian's Perception Scales for the Vibration Serviceability Assessment of an In-Service Glass Walkway. *Appl. Sci.* 2019, 9, 1936. [[CrossRef](#)]



© 2020 by the authors. Licensee MDPI, Basel, Switzerland. This article is an open access article distributed under the terms and conditions of the Creative Commons Attribution (CC BY) license (<http://creativecommons.org/licenses/by/4.0/>).